



08/822962

Case Docket No.PHA 1306

THE COMMISSIONER OF PATENTS AND TRADEMARKS  
Washington, D.C. 20231

Enclosed for filing is the patent application of Inventor(s):  
HAIDEH KHORRAMABADI

For: WIRELESS RECEIVER WITH OFFSET COMPENSATION USING FLASH-ADC

ENCLOSED ARE

[ X ] 11 sheets of [ X ] informal [ ] formal drawings.  
[ X ] An assignment of the invention to PHILIPS ELECTRONICS NORTH  
AMERICA CORPORATION  
[ X ] A fully executed Declaration.  
[ ] An unsigned Declaration.  
[ ] A certified copy of application Serial No.  
[ X ] Associate Power of Attorney.  
[ ] Preliminary Amendment.  
[ ] Information Disclosure Statement and Form PTO-1449.  
[ ] Citation of Related Cases.

FEE COMPUTATION

CLAIMS AS FILED				
FOR	NUMBER FILED	NUMBER EXTRA	RATE	BASIC FEE - \$770.00
Total Claims	15 - 20 =		X \$22 =	
Independent Claims	4 - 3 =	1	X \$80 =	80.00
Multiple Dependent Claims, if any			\$260 =	
TOTAL FILING FEE . . . . .				= \$850.00

Please charge Deposit Account No. 14-1270 in the amount of \$850.00. The Commissioner is hereby authorized to charge any fees which may be required, except the issue fee, or credit any overpayment to Account No. 14-1270.


[ ] Amend the specification by inserting before the first line the sentence: - This is a continuation-in-part of application Serial No. , filed

CERTIFICATE OF EXPRESS MAILING

Express Mail Mailing Label No. EM352555542  
Date of Deposit March 21, 1997  
I hereby certify that this paper and/or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. 1.10 on the date indicated above and is addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231.

Vera Kublanov  
Typed Name

Vera Kublanov  
Signature

  
Jack E. Baker, Reg. #26,902  
Attorney of Record  
(914) 333-9650  
U.S. Philips Corporation  
580 White Plains Road  
Tarrytown, New York 10591  
March 20, 1997

W:\VK\MI20VKA0.FMO

d his

(FILE 'USPAT' ENTERED AT 11:47:56 ON 02 AUG 1998)

L1 4347 S SWITCH####(3W)ZERO##  
L2 16886 S SWITCH####(3A)GROUND###  
L3 70857 S ANALOG##(3W)DIGITAL OR ADC  
L4 137766 S FEEDBACK# OR (FEED OR FED) (1W)BACK#  
L5 2 S L3(P)L1(P)L2 AND L3  
L6 1 S 4654584/PN  
L7 3 S (SETTING OR FIXED OR FIXING OR MAINTAIN###) (7W)L1(P)L2  
L8 1 S (SETTING OR FIXED OR FIXING OR MAINTAIN###) (7W)L4(9W)ZER  
O##  
L9 21 S (SUBTRACT#### OR DIFFERENCE OR ADDING) (8A) (AIN OR VIN OR  
(A  
L10 14 S L9 AND L4  
L11 2 S L9(P)L4  
L12 1 S L9 AND (L1 OR L2)  
L13 0 S SWITCH####(3A)L4(W)LOOP(9W)ZERO##(10W) (GROUND## OR REFER  
ENC

*update search*

his

```
(FILE 'USPAT' ENTERED AT 06:40:41 ON 04 MAR 1998)
L1      67718 S ADC OR ANALOG##(3W)DIGITAL
L2      47920 S DIGITAL(3W)ANALOG## OR DAC
L3      441861 S OFFSET# OR CALIBRAT? OR ERROR#
L4      20126 S L1 AND L2 AND L3
L5      755081 S REGISTER# OR STOR? OR BUFFER
L6      289 S L1(9W)L5(10W)L2
L7      165 S L3 AND L6
L8      117704 S FEEDBACK# OR FEDBACK OR FEED(W)BACK#
L9      57 S L7 AND L8
L10     6 S (3988689 OR 3636463 OR 4308504 OR 4301121 OR 4395681 OR
435
L11     5 S L3 AND L10
L12     5130 S L1(7W)L5
L13     3918 S L5(7W)L2
L14     850 S L12 AND L13
L15     293 S L14 AND L8
L16     377 S L12(P)L13
L17     111 S L8 AND L16
L18     103 S L1(P)L2(P)L3(P)L5(P)L8
L19     24 S L18 AND 341/CLAS
```

his

```
(FILE 'USPAT' ENTERED AT 10:36:58 ON 06 MAR 1998)
L1      67718 S ANALOG##(3W)DIGITAL OR ADC
L2      685827 S REGISTER OR STOR?
L3      388310 S OFFSET# OR ERROR#
L4      47920 S DIGITAL(3W)ANALOG## OR DAC
L5      117 S L2(9W)L4(9W)AMPLIF?
L6      65 S L3 AND L5
L7      3076 S L4(5A)AMPLIF?
L8      4661 S L1(5A)L2
L9      279 S L7 AND L8
L10     202 S L3 AND L9
L11     33711 S RADIO FREQUENCY
L12     5 S L10 AND L11
L13     30 S L10 AND 341/CLAS
```

```
(FILE 'USPAT' ENTERED AT 16:11:43 ON 04 MAR 1998)
      SET PAGELength 99
      SET AUHELP NONE
L1      15451 S FIX###(4W) (ANALOG## OR LEVEL OR INPUT)
L2      71919 S RADIO(W) FREQUENCY OR RF
L3      1186 S L1 AND L2
L4      35 S (ANALOG##(1W) PROCESSOR) (P) (ANALOG##(3W) DIGITAL OR ADC) (P) (D
L5      3 S L1 AND L4
L6      1 S L3 AND L4
L7      53919 S (COMPENSAT? OR CORRECT?) (8A) (OFFSET? OR ERROR#)
L8      220 S L7 AND L3
L9      6 S FIXED INPUT LEVEL
L10     61 S FIX###(1A) (ANALOG OR INPUT) (2A) LEVEL
L11     4 S L7 AND L10 AND L2
L12     0 S L4 AND L10
L13     508 S (CONTROLLING OR CONTROLLER) (4A) (ANALOG OR INPUT) (2A) LEVEL
L14     68 S L7 AND L13
L15     9 S L2 AND L14
L16     47323 S PRECURSOR
=>
```

```
(FILE 'USPAT' ENTERED AT 15:14:51 ON 04 MAR 1998)
      SET PAGELength 99
      SET AUHELP NONE
L1      67718 S ADC OR ANALOG##(3W)DIGITAL
L2      47920 S DIGITAL(3W)ANALOG## OR DAC
L3      638745 S OFFSET? OR CORRECT? OR ERROR# OR CALIBRAT?
L4      12815 S FIX##(3W)(INPUT OR LEVEL OR ANALOG##)
L5      7238 S (CONTROLLER OR CONTROLLING OR CONTROLLED) (6W)ANALOG##
L6      401 S L3(P)L2(P)(L4 OR L5)
L7      303 S L1 AND L6
L8      39 S AUDIO AND L7
L9      33711 S RADIO FREQUENCY
L10     19 S L7 AND L9
=>
```

5. 4,336,534, Jun. 22, 1982, Control generator for use in broadcast receiver including improved signal level indicator; Morio Kumagai, 345/39, 208; 455/159.2 [IMAGE AVAILABLE]

=>

45. 4,476,420, Oct. 9, 1984, Circuit arrangement for synthesizing a sinusoidal position signal having a desired phase and high-resolution positioning system making use of the circuit arrangement; Teruo Asakawa, 318/608; 341/13 [IMAGE AVAILABLE]

46. 4,471,340, Sep. 11, 1984, Analog to digital converter; Bernard L. Lewis, 341/157, 118, 127 [IMAGE AVAILABLE]

47. 4,446,533, May 1, 1984, Stored program digital data processor; Richard J. Backhouse, 711/213; 364/922, 922.4, 926, 926.1, 926.5, 927.8, 928, 933.3, 933.61, 934, 934.71, 937.1, 937.2, 938, 938.3, 947, 947.6, 959.1, 960, 960.2, 964, 964.1, 965, 965.5, DIG.2 [IMAGE AVAILABLE]

48. 4,445,189, Apr. 24, 1984, Analog memory for storing digital information; Gilbert P. Hyatt, 364/600, 862; 365/45, 183; 446/302 [IMAGE AVAILABLE]

49. 4,428,070, Jan. 24, 1984, Dynamic circulation memory; Arthur H. M. van Roermund, et al., 365/222, 73 [IMAGE AVAILABLE]

50. 4,427,973, Jan. 24, 1984, A-To-D converter of the successive-approximation type; Adrian P. Brokaw, et al., 341/134, 154; 377/54 [IMAGE AVAILABLE]

51. 4,400,690, Aug. 23, 1983, A-to-D Converter of the successive-approximation type; Adrian P. Brokaw, et al., 341/134, 154 [IMAGE AVAILABLE]

52. 4,400,689, Aug. 23, 1983, A-to-D Converter of the successive-approximation type; Adrian P. Brokaw, et al., 341/134; 331/57, 111; 341/154 [IMAGE AVAILABLE]

53. 4,388,611, Jun. 14, 1983, Electricity billing meter having unique A/D conversion system; James E. Haferd, 341/122; 327/78, 91; 341/169; 364/178, 179, 483, 487 [IMAGE AVAILABLE]

54. 4,322,819, Mar. 30, 1982, Memory system having servo compensation; Gilbert P. Hyatt, 365/45, 222 [IMAGE AVAILABLE]

55. 4,222,385, Sep. 16, 1980, Electronic heart implant; Richard J. Backhouse, 607/9; 364/916, 916.3, 922, 922.3, 922.4, 926, 926.1, 926.5, 927, 931, 933.3, 933.5, 933.8, 934, 934.1, 935, 935.2, 935.4, 935.6, 937.1, 937.2, 937.4, 938, 938.1, 938.3, 938.4, 939, 939.5, 942.7, 943.9, 943.91, 943.92, 944, 945.4, 945.7, 946.2, 946.6, 946.7, 947, 947.2, 947.3, 947.6, 948.4, 948.91, 949, 949.1, 950, 950.4, 953, 954, 954.1, 954.5, 955, 955.6, 957, 957.1, 960, 960.2, 960.4, 964, 965, 965.5, 965.7, 965.78, 965.8, 966, 966.6, 966.7, DIG.2 [IMAGE AVAILABLE]

56. 4,001,813, Jan. 4, 1977, Precision capacitance to digital conversion system; Henry R. Kosakowski, 341/172; 324/607 [IMAGE AVAILABLE]



=> d 11-56

11. 5,563,597, Oct. 8, 1996, Switched-capacitor one-bit digital-to-analog converter with low sensitivity to op-amp **offset** voltage; Damien McCartney, 341/150, 126, 143 [IMAGE AVAILABLE]
12. 5,535,142, Jul. 9, 1996, Circuit arrangement for an inductive position indicator; Walter Mehnert, et al., 364/559; 33/708; 324/207.15, 207.17, 207.25 [IMAGE AVAILABLE]
13. 5,446,455, Aug. 29, 1995, Auto-calibrated current-mode digital-to-analog converter and method therefor; Todd L. Brooks, 341/145, 118 [IMAGE AVAILABLE]
14. 5,426,431, Jun. 20, 1995, Analog/digital converter; Kazuo Ryu, 341/158, 161 [IMAGE AVAILABLE]
15. 5,410,621, Apr. 25, 1995, Image processing system having a sampled filter; Gilbert P. Hyatt, 382/260; 364/724.011; 382/263 [IMAGE AVAILABLE]
16. 5,373,292, Dec. 13, 1994, Integration type D-A/A-D Conversion apparatus capable of shortening conversion processing time; Akira Yasuda, 341/108, 152, 164, 166 [IMAGE AVAILABLE]
17. 5,339,275, Aug. 16, 1994, Analog memory system; Gilbert P. Hyatt, 365/45, 183, 222, 230.06 [IMAGE AVAILABLE]
18. 5,334,952, Aug. 2, 1994, Fast settling phase locked loop; Steven L. Maddy, et al., 331/1A, 10, 14, 16, 17 [IMAGE AVAILABLE]
19. 5,231,627, Jul. 27, 1993, Apparatus for reading optically encoded soundtracks; Michael W. Paul, et al., 369/125, 120, 124 [IMAGE AVAILABLE]
20. 5,198,785, Mar. 30, 1993, Dual edge pulse width modulation system; Edward P. Jordan, 332/109; 327/176; 375/238 [IMAGE AVAILABLE]
21. 5,154,242, Oct. 13, 1992, Power tools with multi-stage tightening torque control; Koji Soshin, et al., 173/178; 73/862.23, 862.331; 81/469; 173/179, 180 [IMAGE AVAILABLE]
22. 5,136,568, Aug. 4, 1992, Tracking circuit for guiding a beam of light along data tracks of a recorded medium; Friedrich Fuldner, et al., 369/44.25, 44.29, 44.32, 44.34, 54 [IMAGE AVAILABLE]
23. 5,115,172, May 19, 1992, Phase locked loop speed control circuit for controlling speeds and relative positions of objects; Hiroshi Ishii, et al., 318/38; 388/911, 921 [IMAGE AVAILABLE]
24. 5,111,205, May 5, 1992, Digital-to-analog and analog-to-digital converters; Patrice P. Morlon, 341/156, 118, 145, 154, 159 [IMAGE AVAILABLE]
25. 5,053,983, Oct. 1, 1991, Filter system having an adaptive control for updating filter samples; Gilbert P. Hyatt, 364/724.03, 724.04, 724.18 [IMAGE AVAILABLE]
26. 5,014,055, May 7, 1991, Analog-to-digital converter and method of

use utilizing charge redistribution; Andrew G. F. Dingwall, et al., 341/159, 158 [IMAGE AVAILABLE]

27. 4,991,023, Feb. 5, 1991, Microprocessor controlled universal video monitor; Gary H. Nicols, 348/554; 345/213 [IMAGE AVAILABLE]

28. 4,967,197, Oct. 30, 1990, Error correction system for digital to analog converters; Yung-Chow Peng, 341/118, 131, 144 [IMAGE AVAILABLE]

29. 4,910,706, Mar. 20, 1990, Analog memory for storing digital information; Gilbert P. Hyatt, 365/45, 189.01, 222, 230.01; 968/900, DIG.1 [IMAGE AVAILABLE]

30. 4,761,636, Aug. 2, 1988, A-to-D converter of the successive-approximation type; Adrian P. Brokaw, et al., 341/133; 323/281, 313, 907; 327/502, 564, 584; 341/134 [IMAGE AVAILABLE]

31. 4,710,865, Dec. 1, 1987, Control system for positioning an object using switching from a speed control mode to a position control mode with adjustable brain; Makoto Higomura, 364/167.01; 318/592, 594; 364/157, 182, 474.3 [IMAGE AVAILABLE]

32. 4,707,682, Nov. 17, 1987, A-to-D converter of the successive-approximation type; Adrian P. Brokaw, et al., 341/134; 323/281, 313, 907; 341/155 [IMAGE AVAILABLE]

33. 4,686,655, Aug. 11, 1987, Filtering system for processing signature signals; Gilbert P. Hyatt, 367/59; 364/421, 602, 724.011, 728.03; 367/41, 43 [IMAGE AVAILABLE]

34. 4,647,903, Mar. 3, 1987, Successive approximation analog-to-digital converter; Kazuo Ryu, 341/136, 145, 154, 163 [IMAGE AVAILABLE]

35. 4,628,609, Dec. 16, 1986, Incremental measuring and machine control system; Heinz Rieder, et al., 33/707; 250/237G [IMAGE AVAILABLE]

36. 4,622,536, Nov. 11, 1986, Ratio independent cyclic A/D and D/A conversion using a reciprocating reference approach; Cheng-Chung Shih, et al., 341/108, 122, 136, 144, 158, 172 [IMAGE AVAILABLE]

37. 4,581,715, Apr. 8, 1986, Fourier transform processor; Gilbert P. Hyatt, 364/726.01 [IMAGE AVAILABLE]

38. 4,556,870, Dec. 3, 1985, A-To-d converter of the successive-approximation type; Adrian P. Brokaw, et al., 341/119; 323/281, 313, 907; 341/134 [IMAGE AVAILABLE]

39. 4,553,221, Nov. 12, 1985, Digital filtering system; Gilbert P. Hyatt, 364/724.05, 421, 724.04, 728.03 [IMAGE AVAILABLE]

40. 4,553,213, Nov. 12, 1985, Communication system; Gilbert P. Hyatt, 332/185 [IMAGE AVAILABLE]

41. 4,547,766, Oct. 15, 1985, A-To-D converter of the successive-approximation type; Adrian P. Brokaw, et al., 341/134 [IMAGE AVAILABLE]

42. 4,523,290, Jun. 11, 1985, Data processor architecture; Gilbert P. Hyatt, 364/602, 862; 365/1, 222 [IMAGE AVAILABLE]

43. 4,516,177, May 7, 1985, Rotating rigid disk data storage device; William G. Moon, et al., 360/77.07, 77.02, 77.03, 77.05, 77.08 [IMAGE AVAILABLE]

44. 4,491,930, Jan. 1, 1985, Memory system using filterable signals;

16. 4,991,109, Feb. 1991, Image processing system employing pseudo-focal plane array; Rex J. Crookshanks, 345/207, 364/713; 382/254 [IMAGE AVAILABLE]
17. 4,968,970, Nov. 6, 1990, Method of and system for power line carrier communications; Eric LaPorte, 340/310.02, 310.03; 375/258 [IMAGE AVAILABLE]
18. 4,967,197, Oct. 30, 1990, Error correction system for digital to analog converters; Yung-Chow Peng, 341/118, 131, 144 [IMAGE AVAILABLE] ✓
19. 4,965,867, Oct. 23, 1990, Offset compensation circuit; Masami Tsuchida, et al., 341/118, 143 [IMAGE AVAILABLE] ✓
20. 4,817,022, Mar. 28, 1989, Method and apparatus for automatic offset compensation in parameter-sensing transducer systems; Eugene R. Jornod, et al., 364/571.03; 73/1.62, 765, 861.01; 364/558 [IMAGE AVAILABLE]
21. 4,720,992, Jan. 26, 1988, Calibration sequence and method for an electronic compass; Ronald F. Hormel, 73/1.76; 33/356, 361; 364/569, 571.04 [IMAGE AVAILABLE]
22. 4,714,341, Dec. 22, 1987, Multi-wavelength oximeter having a means for disregarding a poor signal; Kenji Hamaguri, et al., 356/41; 600/310 [IMAGE AVAILABLE]
23. 4,689,682, Aug. 25, 1987, Method and apparatus for carrying out television special effects; Richard A. Jackson, 348/578 [IMAGE AVAILABLE]
24. 4,588,983, May 13, 1986, Instantaneous gain changing analog to digital converter; Norman H. Strong, 341/167; 324/99D [IMAGE AVAILABLE] ✓
25. 4,553,052, Nov. 12, 1985, High speed comparator circuit with input-offset compensation function; Kazukiyo Takahashi, 327/65, 69, 91, 215, 307 [IMAGE AVAILABLE]
26. 4,533,952, Aug. 6, 1985, Digital video special effects system; James W. Norman, III, 348/580, 590 [IMAGE AVAILABLE]
27. 4,375,595, Mar. 1, 1983, Switched capacitor temperature independent bandgap reference; Richard W. Ulmer, et al., 327/378; 323/314; 327/480, 539 [IMAGE AVAILABLE]
28. 4,355,285, Oct. 19, 1982, Auto-zeroing operational amplifier circuit; Stephen H. Kelley, et al., 330/9 [IMAGE AVAILABLE]
29. 4,282,515, Aug. 4, 1981, Analog to digital encoding system with an encoder structure incorporating instrumentation amplifier, sample and hold, offset correction and gain correction functions; Raymond B. Patterson, III, 341/118; 327/91; 341/122, 135, 165 [IMAGE AVAILABLE] ✓
30. 3,810,031, May 7, 1974, INTEGRATED AMPLIFYING DEVICE HAVING LOW DRIFT AND METHOD OF COMPENSATING FOR THE DRIFT OF AN AMPLIFYING DEVICE; Robert Poujois, 330/6, 9, 253 [IMAGE AVAILABLE] ✓
31. 3,685,048, Aug. 15, 1972, SELF-CALIBRATING ANALOG TO DIGITAL CONVERTER WITH PREDETERMINED TRANSFER CHARACTERISTICS; Ralph M. Pincus, 341/120, 169 [IMAGE AVAILABLE] ✓

=> d 1-31

1. 5,629,890, May 13, 1997, Integrated circuit system for analog signal storing and recovery incorporating read while writing voltage program method; Lawrence D. Engh, et al., 365/185.03, 45, 185.19, 185.29, 189.07 [IMAGE AVAILABLE]
2. 5,526,502, Jun. 11, 1996, Memory interface; Shinichi Yoshida, et al., 711/202; 345/515; 364/238.4, DIG.1 [IMAGE AVAILABLE]
3. 5,404,089, Apr. 4, 1995, PWM inverter controller with wave form memory; David F. Flanagan, et al., 318/811; 388/907.5 [IMAGE AVAILABLE]
4. 5,400,237, Mar. 21, 1995, PWM inverter controller with waveform memory; David F. Flanagan, et al., 363/41, 37, 95 [IMAGE AVAILABLE]
5. 5,311,085, May 10, 1994, Clocked comparator with offset-voltage compensation; Marcellinus J. M. Pelgrom, et al., 327/65, 94, 199; 330/253 [IMAGE AVAILABLE]
6. 5,283,531, Feb. 1, 1994, Demodulation apparatus incorporating adaptive equalizer for digital communication; Mutsumu Serizawa, et al., 329/316, 318, 327; 375/232; 455/303, 312 [IMAGE AVAILABLE]
7. 5,214,391, May 25, 1993, Demodulation apparatus having multipath detector for selecting a first or second demodulator; Mutsumu Serizawa, et al., 329/316, 318, 327; 375/232, 343, 349; 455/303, 312 [IMAGE AVAILABLE]
8. 5,205,316, Apr. 27, 1993, Air/water volume control system; Kearney L. Pruett, 137/209, 211.5 [IMAGE AVAILABLE]
9. 5,175,802, Dec. 29, 1992, Macro image processing system; Rex J. Crookshanks, 382/278, 281 [IMAGE AVAILABLE]
10. 5,168,398, Dec. 1, 1992, Head positioning control apparatus for a data storage device; Hiroyuki Kanda, et al., 360/78.04, 77.04; 369/44.29 [IMAGE AVAILABLE]
11. 5,159,282, Oct. 27, 1992, Demodulation apparatus incorporating adaptive equalizer for digital communication; Mutsumu Serizawa, et al., 329/316, 318, 327 [IMAGE AVAILABLE]
12. 5,125,008, Jun. 23, 1992, Method and apparatus for autoranging, quadrature signal generation, digital phase reference, and calibration in a high speed RF measurement receiver; Charles D. Trawick, et al., 375/349, 362, 373 [IMAGE AVAILABLE]
13. 5,045,685, Sep. 3, 1991, Analog to digital conversion on multiple channel IC chips; Llewellyn E. Wall, 250/208.1 [IMAGE AVAILABLE]
14. 4,991,127, Feb. 5, 1991, Offset and gain correction system for image data processing; Rex J. Crookshanks, 364/571.04; 348/262 [IMAGE AVAILABLE]
15. 4,991,111, Feb. 5, 1991, Real-time image processing system; Rex J. Crookshanks, 345/507; 364/713; 382/254 [IMAGE AVAILABLE]